

PRODUCT DATA SHEET

Sika® MRA

EMULSION-BASED MOULD RELEASE AGENT

DESCRIPTION

A carefully blended combination of refined mineral oils and emulsifying agents, producing a thin film stable release agent.

USES

Sika® MRA, when applied to steel, plastic and timber formwork, allows clean, fast and easy striking.

CHARACTERISTICS / ADVANTAGES

Sika® MRA provides the following properties:

- Good adhesion to the formwork
- Does not re-emulsify
- Undisturbed by concrete
- Reduces concrete contamination
- Non-inflammable
- MRA is suitable for use on all type of formwork
- All tools can be cleaned with water
- It is an effective rust inhibitor

PRODUCT INFORMATION

Packaging	210 L drum
Appearance / Colour	Milky white
Shelf Life	1 year when unopened
Storage Conditions	Protect from direct sunlight and rain
Density	Approx. 0.97kg/L

APPLICATION INFORMATION

Consumption	Timber: 35 m ² /Liter Steel or plastic: 15 m ² /L
-------------	--

APPLICATION INSTRUCTIONS

APPLICATION

One coat application by brush, roller or spray. Sika® MRA is ready to use and requires no mixing but adequate stirring is advisable. New formwork should be kept dry after Sika® MRA has been applied, it should be protected from rain. Do not water the applied coating even if the surface is dry. Sika® MRA should be allowed to dry before concreting takes place.

Cleaning

Clean all tools, equipment and hands with water.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

ECOLOGY, HEALTH AND SAFETY

For Information and advise on the safe handling, storage and disposal of chemical products, user shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Philippines Inc.
888 Marcos Alvarez Ave.,
Talon V, Las Piñas City, Philippines 1747
Tel. No.: +63 2 8806-2875
Fax. No.:+63 2 8806-2883
Website: phl.sika.com

Product Data Sheet
Sika® MRA
April 2019, Version 01.01
021405021000000094

SikaMRA-en-PH-(04-2019)-1-1.pdf

