

PRODUCT DATA SHEET

Sika® Stabilizer-1518 TBM PH

Foaming agent for TBM - EPBM tunnelling (formerly Sika® Foam TBM 501 LS)

DESCRIPTION

Sika® Stabilizer-1518 TBM PH is a specially designed liquid soil conditioning foaming agent without glycol. It has been formulated to be used with earth pressure balance machines (EPBM) for modifying the properties of the excavated soil particularly in highly cohesive soils.

USES

- Produces a stable foam which can be easily injected into highly cohesive soils during tunnelling operations with earth pressure balance machines (EPBM).
- Especially suitable for the excavation of clay soils or for soil containing not more than 25% to 45% of soils with "granular" behavior.

CHARACTERISTICS / ADVANTAGES

- Modifies properties of the excavated soil.
- Improves the excavation process and TBM performance.
- Can be used in acid and basic soils.
- Lubricating properties minimises friction between soil particles and reduces the cutting wheel torque.
- Prevents clay from plugging.
- Easy to handle and use.
- Normal or hard fresh water can be used to produce the foam.

PRODUCT INFORMATION

Chemical Base	Anionic surfactants and high efficiency polymer
Packaging	210 kg Drum 1000 kg Bulk
Appearance / Colour	Liquid / Clear, slightly yellow
Shelf Life	12 months from date of production
Storage Conditions	Store properly in unopened and undamaged original sealed containers protected from direct sunlight & moisture at temperatures between +5°C and +35°C.
Density	1.050 ± 0.01 kg/L
pH-Value	7-9

APPLICATION INFORMATION

Recommended Dosage

Dosage	~1.5–3.0 %
Foam Expansion Ratio (FER)	~1:2 to 1:20
Foam Injection Ratio (FIR)	~10 % up to 100 %

This information is a guide only and will be specific to each soil type. Preliminary trials in the laboratory must always be carried out to determine foam parameters, such as dosage FER and FIR.

Contact Sika Technical Services for additional information.

Dispensing

Inject through standard TBM dosing and foaming equipment

Restrictions

If separation of the liquid product occurs, mix intensely before using

SYSTEM INFORMATION

Compatibility

Compatible with Sika® admixtures and other Sika® products.
Contact Sika Technical Services for additional information.

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety-related data.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Philippines Inc.
888 Cayetano Avenue,
C5 Extension, Brgy. Palongon - Tipas
Taguig City, Philippines 1630
Telephone no. +63 2 8790-9800
Fax no. +63 2 8790-9828