

## PRODUCT DATA SHEET

# Davco K10 Acrylic Primer

Acrylic primer prior to waterproofing

### DESCRIPTION

Davco K10 Acrylic Primer is used as a primer, sealer and bonding agent to prepare floor surfaces prior to the application of waterproofing membrane & wall-coating system.

### USES

- Primer for Davco K10 Premium and Davco K10 Sovacryl prior to waterproofing of floors/decks and walls

### CHARACTERISTICS / ADVANTAGES

- Reduce dust and increase abrasion resistance of the substrate
- Act as a bonding agent on smooth concrete finishes
- Prime and use as a bonding agent on smooth concrete finishes
- Seal pores on rough porous concrete to eliminate air bubbles

### PRODUCT INFORMATION

Packaging	20L container
Shelf Life	12 months
Storage Conditions	Properly stored in the original unopened container.
Viscosity	(S2, 100rpm). cPs: 18-27
pH-Value	8.5 -10
Consumption	Approx. 0.5 to 1.0 L per M2 (Actual consumption must be verified by user depending on on-site conditions)

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## ECOLOGY, HEALTH AND SAFETY

### SUBSTRATE PREPARATION

- The substrate must be clean, sound, dust-free and without any traces of oil, laitance, curing compound, wax, grease or paint.
- Cementitious substrates must already be sufficiently cured
- Substrate must be dry.

### APPLICATION

- Apply a regular coat using a brush or roller.
- Drying time: 1 - 2 hours depending on the substrate, temperature, and relative humidity.
- DAVCO K10 ACRYLIC PRIMER can be covered as soon as it is touch-dry (tacky).

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Philippines Inc.**  
888 Marcos Alvarez Ave.,  
Talon V, Las Piñas City, Philippines 1747  
Tel. No.: +63 2 8806-2875  
Fax. No.: +63 2 8806-2883  
Website: [phl.sika.com](http://phl.sika.com)

**Product Data Sheet**  
Davco K10 Acrylic Primer  
January 2024, Version 01.01  
02189020000000024

DavcoK10AcrylicPrimer-en-PH-(01-2024)-1-1.pdf

