

PRODUCT DATA SHEET

Sika® Separol®-15 FP PH

OIL BASED, ANTI-CORROSIVE SHUTTER RELEASE AGENT

DESCRIPTION

Sika® Separol®-15 FP PH is an oil based shutter/mould release agent that when applied to formwork provides for clean, fast and easy striking. Suitable for use in hot and tropical climatic conditions.

USES

- Steel shuttering
- Plywood shutters
- High density plastic shutters

CHARACTERISTICS / ADVANTAGES

- Allows clean, easy striking
- Extends the life of formwork
- Improved finish for fair faced concrete
- Reduces concrete contamination
- Economical to use
- Reduces blow hole formation

PRODUCT INFORMATION

Chemical Base	Blend of oil based products.
Packaging	210 L Drum
Shelf Life	24 months from date of production if stored properly.
Storage Conditions	Store in undamaged, unopened, original sealed packaging in dry conditions at temperatures between +5 °C and +45 °C. Protect from direct heat and sunlight.
Appearance / Colour	Light yellowish brown liquid
Specific gravity	Approximately 0.837

APPLICATION INFORMATION

Consumption	Timber: ~25 m ² /kg	~25 m ² /kg
	Steel or plastic: ~50 m ² /kg	~50 m ² /kg
	Coverage depends on wind, humidity and temperature.	

BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

LIMITATIONS

Excess application will tend to run down on vertical surfaces and pool at the bottom.
Remove excess material using a dry cloth or sponge.
Over application may lead to staining of the hardened concrete.
After application to surfaces protect them from rain for at least 2 - 3 hours.

ECOLOGY, HEALTH AND SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Safety Data Sheet (SDS) containing physical, ecological, toxicological and other safety related data.

APPLICATION INSTRUCTIONS

Sika® Separol® FP-15 PH is supplied ready to use. Shutter surfaces must be clean and free from moisture, dirt and laitance.
Apply in one even coat by brush, roller or spray.

LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

Sika Philippines Inc.
888 Marcos Alvarez Ave.,
Talon V, Las Piñas City, Philippines 1747
Tel. No.: +63 2 8806-2875
Fax. No.: +63 2 8806-2883
Website: phl.sika.com

Product Data Sheet
Sika® Separol®-15 FP PH
September 2022, Version 01.01
021405021000000391

SikaSeparol-15FPPH-en-PH-(09-2022)-1-1.pdf