

## PRODUCT DATA SHEET

# SikaProof<sup>®</sup> Tape A+ N

Self-adhesive tape for internal jointing of SikaProof<sup>®</sup> A+ waterproofing system

### DESCRIPTION

SikaProof<sup>®</sup> Tape A+ N is a self-adhesive tape based on a polyacrylate adhesive with a carrier film and a release liner.

### USES

The Product is used for:

- Sealing and bonding overlap joints, connections and details within the SikaProof<sup>®</sup> A+ system.

### CHARACTERISTICS / ADVANTAGES

- Fully and permanently bonded to the concrete structure
- No lateral water underflow between the concrete structure and the membrane system
- High adhesion and good sealing capacity in cold and damp conditions
- Simple and fast to install

### PRODUCT INFORMATION

<b>Packaging</b>	4 rolls packed in one cardboard box	
	Roll length	25 m
	Roll width	(120 ± 5) mm
Refer to the current price list for available packaging variations.		
<b>Appearance / Colour</b>	Top layer	Light grey hybrid bonding layer with yellow waterproofing layer
	Bottom layer	Transparent polyacrylate adhesive covered with transparent release liner
<b>Shelf Life</b>	18 months from date of production	
<b>Storage Conditions</b>	The Product must be stored in original, unopened and undamaged sealed packaging in dry conditions at temperatures between +5 °C and +30 °C. Always refer to packaging.	
<b>Thickness</b>	1.68 mm (+0.17 mm / -0.08 mm)	

### APPLICATION INFORMATION

<b>Ambient Air Temperature</b>	Maximum	+45 °C
	Minimum	+5 °C
<b>Substrate Temperature</b>	Minimum	+5 °C

### SYSTEM INFORMATION

---

**System Structure**

SikaProof® Tape A+ N is a system component for internal jointing of the SikaProof® A+ system. For more detailed information, refer to Sika® Method Statement: Method Statement SikaProof® A+

---

## BASIS OF PRODUCT DATA

All technical data stated in this Product Data Sheet are based on laboratory tests. Actual measured data may vary due to circumstances beyond our control.

## FURTHER DOCUMENTS

Refer to the following Sika® Method Statements:

- Method Statement SikaProof® A+
- Application manual SikaProof® A+

## ECOLOGY, HEALTH AND SAFETY

We follow PLC -Priority Chemical List and PICCS- Philippine Inventory of Chemicals and Chemical Substances but we don't indicate on our local PDS.

## APPLICATION INSTRUCTIONS

### SUBSTRATE QUALITY

The contact surface is the grey SikaProof® A+ bonding layer. It must be dry or slightly damp, clean and free of any materials that could impair adhesion.

#### **Application outside of specified application conditions**

Note: Under certain circumstances, the Product can be applied in conditions other than the ones specified in this data sheet. However, this requires specific precautions and application methods.

1. Contact Sika technical services for more information.

## APPLICATION

### IMPORTANT

#### **Strictly follow installation procedures**

Strictly follow installation procedures as defined in Method Statements, application manuals and working instructions which must always be adjusted to the actual site conditions.

### IMPORTANT

#### **Application by trained personnel**

The application of this Product must only be carried out by an applicator that is trained or approved by Sika. The applicator must also be experienced in this type of application.

### IMPORTANT

#### **Exposure to UV or weathering**

The Product is not resistant to permanent UV exposure or weathering.

1. Protect as soon as possible but not later than 90 days after application
1. Remove the release liner
2. Apply onto the grey SikaProof® A+ membrane side
3. Press on firmly using a pressure roller

## LOCAL RESTRICTIONS

Please note that as a result of specific local regulations the performance of this product may vary from country to country. Please consult the local Product Data Sheet for the exact description of the application fields.

## LEGAL NOTES

The information, and, in particular, the recommendations relating to the application and end-use of Sika products, are given in good faith based on Sika's current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance with Sika's recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. Sika reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.

**Sika Philippines Inc.**  
888 Cayetano Avenue,  
C5 Extension, Brgy. Palongon - Tipas  
Taguig City, Philippines 1630  
Telephone no. +63 2 8790-9800  
Fax no. +63 2 8790-9828

**Product Data Sheet**  
**SikaProof® Tape A+ N**  
February 2025, Version 02.01  
020720308000000021

SikaProofTapeA+N-en-PH-(02-2025)-2-1.pdf

